

Display Elektronik GmbH

DATA SHEET

TFT MODULE

**DEM 800320A2 TMH-PW-N
(A-TOUCH)**

4,6" TFT + TP

Product Specification

Ver.: 1

08.05.2018

Revision History

| Revision | Date | Originator | Detail | Remarks |
|-----------------|-------------|-------------------|---|----------------------|
| 0 | 09.03.2018 | MH | Initial Release | - |
| 1 | 08.05.2018 | MH | Modify Optical Characteristics Modify Many Details | P7 P6/P15/P21/P22 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Table of Contents

| No. | Item | Page |
|-------|--|------|
| 1. | General Description | 4 |
| 2. | Module Parameter..... | 4 |
| 3. | Absolute Maximum Ratings | 4 |
| 4. | DC Characteristics | 5 |
| 5. | Backlight Characteristic..... | 5 |
| 5.1. | Backlight Characteristics | 5 |
| 5.2. | Backlighting circuit | 5 |
| 6. | Touch Screen Panel Specifications..... | 6 |
| 7. | Optical Characteristics | 7 |
| 7.1. | Optical Characteristics..... | 7 |
| 7.2. | Definition of Response Time..... | 7 |
| 7.3. | Definition of Contrast Ratio | 8 |
| 7.4. | Definition of Viewing Angles | 8 |
| 7.5. | Definition of Color Appearance | 9 |
| 7.6. | Definition of Surface Luminance, Uniformity and Transmittance..... | 9 |
| 8. | Block Diagram and Power Supply | 10 |
| 9. | Interface Pins Definition | 11 |
| 10. | Timing Chart..... | 12 |
| 10.1. | Data Input Format..... | 12 |
| 10.2. | Timing Parameters..... | 12 |
| 10.3. | Input Clock and Data Timing Diagram..... | 13 |
| 11. | Quality Assurance | 14 |
| 11.1 | Purpose..... | 14 |
| 11.2 | Standard for Quality Test..... | 14 |
| 11.3 | Nonconforming Analysis & Disposition | 14 |
| 11.4 | Agreement Items | 14 |
| 11.5 | Standard of the Product Visual Inspection | 15 |
| 11.6 | Inspection Specification | 16 |
| 11.7 | Classification of Defects..... | 20 |
| 11.8 | Identification/marketing criteria | 20 |
| 11.9 | Packing | 21 |
| 12. | Reliability Specification | 22 |
| 13. | Precautions and Warranty..... | 23 |
| 13.1 | Safety..... | 23 |
| 13.2 | Handling..... | 23 |
| 13.3 | Storage..... | 23 |
| 13.4 | Metal Pin (Apply to Products with Metal Pins)..... | 23 |
| 13.5 | Operation | 25 |
| 13.6 | Static Electricity..... | 25 |
| 13.7 | Limited Warranty..... | 25 |
| 14. | Outline Drawing..... | 26 |

1. General Description

The specification is a transmissive type color active matrix liquid crystal display (LCD) which uses amorphous thin film transistor (TFT) as switching devices. This product is composed of a TFT-LCD panel, driver ICs, a touch panel and a backlight unit.

2. Module Parameter

| Features | Details | Unit |
|--------------------------------|--------------------------------|------------|
| Display Size (Diagonal) | 4.6" | - |
| LCD Type | TN TFT | - |
| Display Mode | Normally White / Transmissive | - |
| Resolution | 800 x RGB x 320 | Pixels |
| View Direction | 12 O'clock | Best Image |
| Gray Scale Inversion Direction | 6 O'clock | - |
| Module Outline | 120.70 x 57.08 x 4.35 (Note1) | mm |
| Active Area | 108.00 x 43.20 | mm |
| Pixel Size | 0.135 x 0.135 | mm |
| Pixel Arrangement | R.G.B Vertical Stripe | - |
| Polarizer Surface Treatment | Anti-Glare | - |
| Driver IC | ILI6126C & ILI5960D | - |
| Display Colors | 16.7 Million | - |
| Interface | 24-Bit RGB Interface | - |
| With or Without Touch Panel | With Resistive Touch | - |
| Operating Temperature | -20°C to +70°C | °C |
| Storage Temperature | -30°C to +80°C | °C |
| Weight | 57 | g |

Note 1: Exclusive hooks, posts, FFC/FPC tail etc.

3. Absolute Maximum Ratings

$V_{SS}=0V$, $T_a=25^{\circ}C$

| Item | Symbol | Min. | Max. | Unit |
|-----------------------|------------------|------|------|------|
| Supply Voltage | VDD | -0.5 | 5.0 | V |
| Storage Temperature | T _{STG} | -30 | +80 | °C |
| Operating Temperature | T _{OP} | -20 | +70 | °C |

Note 1: If T_a below +50°C, the maximal humidity is 90%RH, if T_a over +50°C, absolute humidity should be less than 60%RH.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C, and the back ground will become darker at high temperature operating.

4. DC Characteristics

| Item | Symbol | Min. | Typ. | Max. | Unit |
|---------------------------|---------------------------------|---------|--------|---------|------|
| Supply Voltage | VDD | 2.7 | 3.3 | 3.6 | V |
| Logic Low Input Voltage | V _{IL} | GND | - | 0.3*VDD | V |
| Logic High Input Voltage | V _{IH} | 0.7*VDD | - | VDD | V |
| Logic Low Output Voltage | V _{OL} | - | - | GND+0.4 | V |
| Logic High Output Voltage | V _{OH} | VDD-0.4 | - | - | V |
| Current Consumption | I _{CC+ I_{IN}} | - | t.b.d. | - | mA |
| All Black | | | | | |
| | Analog | | | | |


5. Backlight Characteristic

5.1. Backlight Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|----------------------|---|------------------------------------|-------|-------|------|------|
| Forward Voltage | V _F | Ta=25 °C, I _F =20mA/LED | 16.8 | 19.2 | 20.4 | V |
| Forward Current | I _F | Ta=25 °C, V _F =3.2V | - | 60 | - | mA |
| Power Dissipation | P _D | | - | 1152 | - | mW |
| LED Lifetime (+25°C) | - | - | 20000 | 30000 | - | Hr |
| Uniformity | Avg | | - | 80 | - | % |
| Drive Method | Constant current | | | | | |
| LED Configuration | 18 White LEDs (6 LEDs in one string and 3 groups in parallel) | | | | | |

Note: LED life time defined as follows: The final brightness is at 70% of original brightness.
 The environmental conducted under ambient air flow, at Ta=25°C±2°C, 60%RH±5%, I_F≤20mA.

5.2. Backlighting Circuit



6. Touch Screen Panel Specifications**6.1 Electrical Characteristics**

| Item | Min. | Typ. | Max. | Unit | Note |
|-----------------------|------|------|------|------------|---------------------------|
| Linearity | -1.5 | | 1.5 | % | Analog X and Y directions |
| Terminal Resistance | 300 | | 1350 | Ω | X (Glass side) |
| | 100 | | 450 | Ω | Y (Film side) |
| Insulation Resistance | (20) | - | - | M Ω | |
| Voltage | - | - | 5 | V | DC |
| Chattering | - | - | 15 | ms | |

Caution (1): Do not operate it with a thing except a polyacetal pen (tip R0.8mm or less) or a finger, especially those with hard or sharp tips such as a ball point pen or a mechanical pencil.

Caution (2): RTP operation must be followed the parameter condition.

Caution (3): If ask for use glare ITO film, it may result in Newton issue.

6.2 Mechanical & Reliability Characteristics

| Item | Min. | Typ. | Max. | Unit | Note |
|-------------------------------|-----------------|------|------|------------|------|
| Activation Force | (20) | - | 100 | g | (1) |
| Durability-Surface Scratching | Write 20,000 | - | - | characters | (2) |
| Durability-Surface Pitting | 1,000,000 | - | - | touches | (3) |
| Surface Hardness | 3 | - | - | H | |

Note (1) Stylus pen Input: R0.8mm polyacetal pen or Finger nail.

Note (2) Measurement for Surface area

- Force: 150-250gf
- Speed: 60mm/sec
- Stylus: R0.8 polyacetal pen or Finger nail.

Note (3) Pit 1,000,000 times on the Film with a R3.75 silicon rubber.

- Force: Force: 2.45N
- Speed: 3times/sec

7. Optical Characteristics


7.1. Optical Characteristics

Ta=25°C, V_{DD} =3.3V

| | Item | Symbol | Condition | Specification | | | Unit | |
|----------------------------------|--|-----------------|---|---------------|-------|-------|-------------------|------|
| | | | | Min. | Typ. | Max. | | |
| Backlight On (Transmissive Mode) | Luminance on TFT(I _f =20mA/LED) | Lv | Normally viewing angle θ _X = φ _Y =0° | 320 | 400 | - | cd/m ² | |
| | Contrast Ratio(See 6.3) | CR | | - | 350 | - | | |
| | Response Time (See 6.2) | TR+TF | | - | 20 | - | ms | |
| | Chromaticity Transmissive (See 6.5) | Red | X _R | Center CR≥10 | 0.552 | 0.602 | 0.652 | |
| | | | Y _R | | 0.312 | 0.362 | 0.412 | |
| | | Green | X _G | | 0.261 | 0.311 | 0.361 | |
| | | | Y _G | | 0.576 | 0.626 | 0.676 | |
| | | Blue | X _B | | 0.097 | 0.147 | 0.197 | |
| | | | Y _B | | 0.093 | 0.143 | 0.193 | |
| | White | X _W | 0.229 | 0.279 | 0.329 | | | |
| | | Y _W | 0.312 | 0.362 | 0.412 | | | |
| | Viewing Angle (See 6.4) | Horizontal | θ _{X+} | Center CR≥10 | 60 | 65 | - | Deg. |
| | | | θ _{X-} | | 60 | 65 | - | |
| Vertical | | φ _{Y+} | 45 | | 50 | - | | |
| | | φ _{Y-} | 55 | | 60 | - | | |
| NTSC Ratio(Gamut) | | | | - | 50 | - | % | |

7.2. Definition of Response Time

7.2.1. Normally Black Type (Negative)




Tr is the time it takes to change from non-selected stage with relative luminance 10% to selected state with relative luminance 90%;

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%

Note: Measuring machine: LCD-5100

7.2.2. Normally White Type (Positive)



Tr is the time it takes to change from non-selected stage with relative luminance 90% to selected state with relative luminance 10%;

Tf is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%;

Note: Measuring machine: LCD-5100 or EQUI

7.3. Definition of Contrast Ratio


Contrast is measured perpendicular to display surface in reflective and transmissive mode.

The measurement condition is:

| | |
|--------------------------|--------------------------|
| Measuring Equipment | Eldim or Equivalent |
| Measuring Point Diameter | 3mm//1mm |
| Measuring Point Location | Active Area centre point |
| Test pattern | A: All Pixels white |
| | B: All Pixel black |
| Contrast setting | Maximum |

Definitions: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

7.4. Definition of Viewing Angles




Measuring machine: LCD-5100 or EQUI

7.5. Definition of Color Appearance

R,G,B and W are defined by (x, y) on the IE chromaticity diagram

NTSC=area of RGB triangle/area of NTSC triangleX100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)




7.6. Definition of Surface Luminance, Uniformity and Transmittance


Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.

- 7.6.1. Surface Luminance: $L_v = \text{average} (L_{P1}:L_{P9})$
- 7.6.2. Uniformity = $\text{Minimal} (L_{P1}:L_{P9}) / \text{Maximal} (L_{P1}:L_{P9}) * 100\%$
- 7.6.3. Transmittance = $L_v \text{ on LCD} / L_v \text{ on Backlight} * 100\%$

Note: Measuring machine: BM-7



8. Block Diagram and Power Supply




9. Interface Pins Definition

| No. | Symbol | Function | Remark |
|------------|---------------|--|---------------|
| 1 | VLED- | Ground(Cathode) | |
| 2 | VLED+ | LED Input Terminal(Anode) | |
| 3 | GND | Power voltage | |
| 4 | VDD | Power voltage | |
| 5 | R0 | Red data(LSB) | |
| 6 | R1 | Red data | |
| 7 | R2 | Red data | |
| 8 | R3 | Red data | |
| 9 | R4 | Red data | |
| 10 | R5 | Red data | |
| 11 | R6 | Red data | |
| 12 | R7 | Red data(MSB) | |
| 13 | G0 | Green data(LSB) | |
| 14 | G1 | Green data | |
| 15 | G2 | Green data | |
| 16 | G3 | Green data | |
| 17 | G4 | Green data | |
| 18 | G5 | Green data | |
| 19 | G6 | Green data | |
| 20 | G7 | Green data(MSB) | |
| 21 | B0 | Blue data(LSB) | |
| 22 | B1 | Blue data | |
| 23 | B2 | Blue data | |
| 24 | B3 | Blue data | |
| 25 | B4 | Blue data | |
| 26 | B5 | Blue data | |
| 27 | B6 | Blue data | |
| 28 | B7 | Blue data(MSB) | |
| 29 | GND | Ground | |
| 30 | CLKIN | Clock for input data. Data latched at rising edge of this signal | |
| 31 | STBYB | Display on/off | |
| 32 | HSD | Horizontal sync signal | |
| 33 | VSD | Vertical sync signal | |
| 34 | DEN | Data enable. (In SYNC mode this pin should not be used.) | |
| 35 | NC | No connection | |
| 36 | GND | Ground | |
| 37 | NC(XR) | Touch panel terminal. | |
| 38 | NC(YD) | Touch panel terminal. | |
| 39 | NC(XL) | Touch panel terminal. | |
| 40 | NC(YU) | Touch panel terminal. | |


10. Timing Chart

10.1.Data Input Format

Vertical input Format



Horizontal input timing



10.2.Timing Parameters


Horizontal Input Timing

| Parameter | Symbol | Value | | | Unit |
|---------------------------|--------|-------|------|------|------|
| | | Min. | Typ. | Max. | |
| Horizontal Display Area | thd | 800 | | | DCLK |
| DCLK Frequency | fclk | - | 30 | - | MHZ |
| 1 Horizontal Line | th | 898 | | | DCLK |
| HSD Pulse Width | Min. | 1 | | | |
| | Typ. | 2 | | | |
| | Max. | - | | | |
| HSD Back Porch (Blanking) | thb | - | 88 | - | |
| HSD Front Porch | thfp | - | 10 | - | |

Vertical Input Timing

| Parameter | Symbol | Value | | | Unit |
|---------------------------|--------|-------|------|------|------|
| | | Min. | Typ. | Max. | |
| Vertical Display Area | tvd | 320 | | | H |
| VSD Period Time | tv | - | 524 | - | H |
| VSD Pulse Width | tpw | - | 2 | - | H |
| VSD Back Porch (Blanking) | tvb | - | 191 | - | H |
| VSD Front Porch | tvfp | - | 13 | - | H |

10.3. Input Clock and Data Timing Diagram



Parallel 24-bit RGB mode

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Conditions |
|--------------------------------|--------|------|------|------|-------|------------------|
| CLKIN Frequency | Fclk | - | 33 | 50 | MHz | VDD = 2.7V ~3.6V |
| CLKIN Cycle Time | Tclk | 20 | 30 | - | ns | |
| CLKIN Pulse Duty | Tcwh | 40 | 50 | 60 | % | Tclk |
| Time from HSD to Source Output | Thso | - | 64 | - | CLKIN | |
| Time from HSD to LD | Thld | - | 64 | - | CLKIN | |
| Time from HSD to STV | Thstv | - | 2 | - | CLKIN | |
| Time from HSD to CKV | Thckv | - | 20 | - | CLKIN | |
| Time from HSD to OEV | Thoev | - | 4 | - | CLKIN | |
| LD Pulse Width | Twd | - | 10 | - | CLKIN | |
| CKV Pulse Width | Twckv | - | 66 | - | CLKIN | |
| OEV Pulse Width | Twoev | - | 92 | - | CLKIN | |

11. Quality Assurance

11.1 Purpose

This standard for Quality Assurance assures the quality of LCD module products supplied to customer.

11.2 Standard for Quality Test

11.2.1 Sampling Plan:

GB2828.1-2012

Single sampling, normal inspection

11.2.2 Sampling Criteria:

Visual inspection: AQL 1.5%

Electrical functional: AQL 0.65%.

11.2.3 Reliability Test:

Detailed requirement refer to Reliability Test Specification.

11.3 Nonconforming Analysis & Disposition

11.3.1 Nonconforming analysis:

11.3.1.1 Customer should provide overall information of non-conforming sample for their complaints.

11.3.1.2 After receipt of detailed information from customer, the analysis of nonconforming parts usually should be finished in one week.

11.3.1.3 If cannot finish the analysis on time, customer will be notified with the progress status.

11.3.2 Disposition of nonconforming:

11.3.2.1 Non-conforming product over PPM level will be replaced.

11.3.2.2 The cause of non-conformance will be analyzed. Corrective action will be discussed and implemented.

11.4 Agreement Items

Shall negotiate with customer if the following situation occurs:

11.4.1 There is any discrepancy in standard of quality assurance.

11.4.2 Additional requirement to be added in product specification.

11.4.3 Any other special problem.


11.5 Standard of the Product Visual Inspection

11.5.1 Appearance inspection:

11.5.1.1 The inspection must be under illumination about 1000 – 1500 lx, and the distance of view must be at 30cm ± 2cm.

11.5.1.2 The viewing angle should be 45° from the vertical line without reflection light or follows customer's viewing angle specifications.

11.5.1.3 Definition of area: A Zone: Active Area, B Zone: Viewing Area,







11.5.2 Basic principle:





11.5.2.1 A set of sample to indicate the limit of acceptable quality level must be discussed by both us and customer when there is any dispute happened.


11.5.2.2 New item must be added on time when it is necessary.

11.6 Inspection Specification

| No. | Item | Criteria (Unit: mm) | | | | | | | | | | | | | | | | | | |
|-------------------------|---|---|--|-------------|--------------|------------------|--------|-------------------------|---|-------------------------|----------|---------------|------------|-----------|-------------------------------|------------|--------|------|------------------------------------|--|
| 01 | Black / White spot Foreign material (Round type) Pinholes Stain Particles inside cell. (Minor defect) |  <p>$\phi = (a + b) / 2$ Distance between 2 defects should more than 5mm apart.</p> | <table border="1"> <thead> <tr> <th data-bbox="922 347 1177 425">Size \ Area</th> <th data-bbox="1177 347 1426 425">Acc. Qty</th> </tr> </thead> <tbody> <tr> <td data-bbox="922 425 1177 470">$\phi \leq 0.10$</td> <td data-bbox="1177 425 1426 470">Ignore</td> </tr> <tr> <td data-bbox="922 470 1177 515">$0.10 < \phi \leq 0.15$</td> <td data-bbox="1177 470 1426 515">2</td> </tr> <tr> <td data-bbox="922 515 1177 560">$0.15 < \phi \leq 0.25$</td> <td data-bbox="1177 515 1426 560">1</td> </tr> <tr> <td data-bbox="922 560 1177 604">$0.25 < \phi$</td> <td data-bbox="1177 560 1426 604">0</td> </tr> <tr> <td data-bbox="922 604 1177 683">Total</td> <td data-bbox="1177 604 1426 683">2 no include $\phi \leq 0.10$</td> </tr> </tbody> </table> | Size \ Area | Acc. Qty | $\phi \leq 0.10$ | Ignore | $0.10 < \phi \leq 0.15$ | 2 | $0.15 < \phi \leq 0.25$ | 1 | $0.25 < \phi$ | 0 | Total | 2 no include $\phi \leq 0.10$ | | | | | |
| Size \ Area | Acc. Qty | | | | | | | | | | | | | | | | | | | |
| $\phi \leq 0.10$ | Ignore | | | | | | | | | | | | | | | | | | | |
| $0.10 < \phi \leq 0.15$ | 2 | | | | | | | | | | | | | | | | | | | |
| $0.15 < \phi \leq 0.25$ | 1 | | | | | | | | | | | | | | | | | | | |
| $0.25 < \phi$ | 0 | | | | | | | | | | | | | | | | | | | |
| Total | 2 no include $\phi \leq 0.10$ | | | | | | | | | | | | | | | | | | | |
| 02 | Electrical Defect (Minor defect) | <table border="1"> <thead> <tr> <th data-bbox="518 784 826 862">Bright dot</th> <th data-bbox="826 784 1045 862">Display Area</th> <th data-bbox="1045 784 1248 862">Total</th> <th data-bbox="1248 784 1385 996" rowspan="3">Note1</th> </tr> </thead> <tbody> <tr> <td data-bbox="518 862 826 907"></td> <td data-bbox="826 862 1045 907">0</td> <td data-bbox="1045 862 1248 907">0</td> </tr> <tr> <td data-bbox="518 907 826 952">Dark dot</td> <td data-bbox="826 907 1045 952">$N \leq 2$</td> <td data-bbox="1045 907 1248 952">$N \leq 2$</td> </tr> <tr> <td data-bbox="518 952 826 996">Total dot</td> <td data-bbox="826 952 1045 996">$N \leq 2$</td> <td data-bbox="1045 952 1248 996">$N \leq 2$</td> <td data-bbox="1248 996 1385 1097" rowspan="2">Note 2</td> </tr> <tr> <td data-bbox="518 996 826 1097">Mura</td> <td colspan="2" data-bbox="826 996 1248 1097">Not visible through 5% ND filters.</td> </tr> </tbody> </table> <p>Remark: 1. Bright dot caused by scratch and foreign object accords to item 1.</p> | | Bright dot | Display Area | Total | Note1 | | 0 | 0 | Dark dot | $N \leq 2$ | $N \leq 2$ | Total dot | $N \leq 2$ | $N \leq 2$ | Note 2 | Mura | Not visible through 5% ND filters. | |
| Bright dot | Display Area | Total | Note1 | | | | | | | | | | | | | | | | | |
| | 0 | 0 | | | | | | | | | | | | | | | | | | |
| Dark dot | $N \leq 2$ | $N \leq 2$ | | | | | | | | | | | | | | | | | | |
| Total dot | $N \leq 2$ | $N \leq 2$ | Note 2 | | | | | | | | | | | | | | | | | |
| Mura | Not visible through 5% ND filters. | | | | | | | | | | | | | | | | | | | |

| <p>3</p> | <p>Black and White line Scratch Foreign material (Line type) (Minor defect)</p> |  <table border="1" data-bbox="577 761 1204 1025"> <thead> <tr> <th>Length</th> <th>Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>/</td> <td>$W \leq 0.1$</td> <td>Ignore</td> </tr> <tr> <td>$L \leq 2.5$</td> <td>$0.1 < W \leq 0.2$</td> <td>3</td> </tr> <tr> <td>$L > 2.5$</td> <td>$0.2 < W$</td> <td>0</td> </tr> <tr> <td colspan="2">Total</td> <td>3</td> </tr> </tbody> </table> <p>Distance between 2 defects should more than 3mm apart. Scratches not viewable through the back of the display are acceptable.</p> | Length | Width | Acc. Qty | / | $W \leq 0.1$ | Ignore | $L \leq 2.5$ | $0.1 < W \leq 0.2$ | 3 | $L > 2.5$ | $0.2 < W$ | 0 | Total | | 3 |
|------------------------------|--|--|------------------|----------|--------------------|---|--------------------|--------|------------------------------|--------------------|---|-----------|-----------|---|-------|--|---|
| Length | Width | Acc. Qty | | | | | | | | | | | | | | | |
| / | $W \leq 0.1$ | Ignore | | | | | | | | | | | | | | | |
| $L \leq 2.5$ | $0.1 < W \leq 0.2$ | 3 | | | | | | | | | | | | | | | |
| $L > 2.5$ | $0.2 < W$ | 0 | | | | | | | | | | | | | | | |
| Total | | 3 | | | | | | | | | | | | | | | |
| <p>04</p> | <p>Glass Crack (Minor defect)</p> |  <p>Crack is potential to enlarge, any type is not allowed.</p> | | | | | | | | | | | | | | | |
| <p>05</p> | <p>Glass Chipping Pad Area: (Minor defect)</p>  | <table border="1" data-bbox="874 1624 1343 1792"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>3</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 3 | $a < \text{Glass Thickness}$ | | | | | | | | |
| Length and Width | Acc. Qty | | | | | | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 3 | | | | | | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | | | | | | |

| <p>06</p> | <p>Glass Chipping Rear of Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">a < Glass Thickness</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | a < Glass Thickness | |
|---------------------|--|--|------------------|----------|--------------------|--------|---------------------|---|--------------------|---|---------------------|--|
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| a < Glass Thickness | | | | | | | | | | | | |
| <p>07</p> | <p>Glass Chipping Except Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">a < Glass Thickness</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | a < Glass Thickness | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| a < Glass Thickness | | | | | | | | | | | | |
| <p>08</p> | <p>Glass Corner Chipping: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c < 3.0, b < 3.0$</td> <td>Ignore</td> </tr> <tr> <td colspan="2">a < Glass Thickness</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c < 3.0, b < 3.0$ | Ignore | a < Glass Thickness | | | | | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c < 3.0, b < 3.0$ | Ignore | | | | | | | | | | | |
| a < Glass Thickness | | | | | | | | | | | | |
| <p>9</p> | <p>Glass Burr: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$F < 1.0$</td> <td>Ignore</td> </tr> </tbody> </table> <p>Glass burr don't affect assemble and module dimension.</p> | Length | Acc. Qty | $F < 1.0$ | Ignore | | | | | | |
| Length | Acc. Qty | | | | | | | | | | | |
| $F < 1.0$ | Ignore | | | | | | | | | | | |

| 10 | <p>FPC Defect: (Minor defect)</p>  | <p>10.1 Dent, pinhole width $a < w/3$. (w: circuitry width.)</p> <p>10.2 Open circuit is unacceptable.</p> <p>10.3 No oxidation, contamination and distortion.</p> | | | | | | | | |
|----------------------------|---|--|----------|----------|---------------------|--------|----------------------------|------------|------------------|---------|
| 11 | <p>Bubble on Polarizer (Minor defect)</p> | <table border="1"> <thead> <tr> <th>Diameter</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$\varphi \leq 0.30$</td> <td>Ignore</td> </tr> <tr> <td>$0.30 < \varphi \leq 0.50$</td> <td>$N \leq 2$</td> </tr> <tr> <td>$0.50 < \varphi$</td> <td>$N = 0$</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.30$ | Ignore | $0.30 < \varphi \leq 0.50$ | $N \leq 2$ | $0.50 < \varphi$ | $N = 0$ |
| Diameter | Acc. Qty | | | | | | | | | |
| $\varphi \leq 0.30$ | Ignore | | | | | | | | | |
| $0.30 < \varphi \leq 0.50$ | $N \leq 2$ | | | | | | | | | |
| $0.50 < \varphi$ | $N = 0$ | | | | | | | | | |
| 12 | <p>Dent on Polarizer (Minor defect)</p> | <table border="1"> <thead> <tr> <th>Diameter</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$\varphi \leq 0.25$</td> <td>Ignore</td> </tr> <tr> <td>$0.25 < \varphi \leq 0.50$</td> <td>$N \leq 4$</td> </tr> <tr> <td>$0.50 < \varphi$</td> <td>None</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.25$ | Ignore | $0.25 < \varphi \leq 0.50$ | $N \leq 4$ | $0.50 < \varphi$ | None |
| Diameter | Acc. Qty | | | | | | | | | |
| $\varphi \leq 0.25$ | Ignore | | | | | | | | | |
| $0.25 < \varphi \leq 0.50$ | $N \leq 4$ | | | | | | | | | |
| $0.50 < \varphi$ | None | | | | | | | | | |
| 13 | <p>Bezel</p> | <p>13.1 No rust, distortion on the Bezel.</p> <p>13.2 No visible fingerprints, stains or other contamination.</p> | | | | | | | | |
| 14 | <p>Touch Panel</p> | <p>D: Diameter W: width L: length</p> <p>14.1 Spot: $D < 0.25$ is acceptable $0.25 \leq D \leq 0.4$</p> <p>2dots are acceptable and the distance between defects should more than 10 mm.</p> <p>$D > 0.4$ is unacceptable</p> <p>14.2 Dent: $D > 0.40$ is unacceptable</p> <p>14.3 Scratch: $W \leq 0.03$, $L \leq 10$ is acceptable, $0.03 < W \leq 0.10$, $L \leq 10$ is acceptable</p> <p>Distance between 2 defects should more than 10 mm.</p> <p>$W > 0.10$ is unacceptable.</p> | | | | | | | | |
| 15 | <p>LCD Ripple</p> | <p>Touch the touch panel, cannot see the LCD ripple.</p> <p>Pen: R 0.8mm silicon rubber.</p> <p>Operation Force: TBD g</p> | | | | | | | | |

| | | |
|----|-------------------------------------|--|
| 16 | PCB | 16.1 No distortion or contamination on PCB terminals. 16.2 All components on PCB must same as documented on the BOM/component layout. 16.3 Follow IPC-A-600F. |
| 17 | Soldering | Follow IPC-A-610C standard |
| 18 | Electrical Defect (Major defect) | The below defects must be rejected. 18.1 Missing vertical / horizontal segment, 18.2 Abnormal Display. 18.3 No function or no display. 18.4 Current exceeds product specifications. 18.5 LCD viewing angle defect. 18.6 No Backlight. 18.7 Dark Backlight. 18.8 Touch Panel no function. |

Remark: LCD Panel Broken shall be rejected. Defect out of LCD viewing area is acceptable.

11.7 Classification of Defects

11.7.1 Visual defects (Except no / wrong label) are treated as minor defect and electrical defect is major.

11.7.2 Two minor defects are equal to one major in lot sampling inspection.


11.8 Identification/marketing criteria

Any unit with illegible / wrong /double or no marking/ label shall be rejected.

11.9 Packing

- 11.9.1 There should be no damage of the outside carton box, each packaging box should have one identical label.
- 11.9.2 Modules inside package box should have compliant mark.
- 11.9.3 All direct package materials shall offer ESD protection

Note1: Bright dot is defined as the defective area of the dot is larger than 50% of one sub-pixel area.



Bright dot: The bright dot size defect at black display pattern. It can be recognized by 2% transparency of filter when the distance between eyes and panel is $350\text{mm} \pm 50\text{mm}$.

Dark dot: Cyan, Magenta or Yellow dot size defect at white display pattern. It can be recognized by 5% transparency of filter when the distance between eyes and panel is $350\text{mm} \pm 50\text{mm}$.

Note2: Mura on display which appears darker / brighter against background brightness on parts of display area.

12. Reliability Specification

| No | Item | Condition | Quantity | Criteria |
|----|-----------------------------|---|----------|------------------|
| 1 | High Temperature Operating | +70°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 2 | Low Temperature Operating | -20°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 3 | High Humidity | +50°C, 90%RH, 96Hrs | 2 | GB/T2423.3-2006 |
| 4 | High Temperature Storage | +80°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 5 | Low Temperature Storage | -30°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 6 | Thermal Cycling Test | -20°C, 60min~+70°C, 60min, 20 cycles. | 2 | GB/T2423.22-2012 |
| 7 | Packing Vibration | Frequency range:10Hz~50Hz Acceleration of gravity:5G X, Y, Z 30 min for each direction. | 2 | GB/T5170.14-2009 |
| 8 | Electrical Static Discharge | Air: ±8KV 150pF/330Ω 5 times | 2 | GB/T17626.2-2006 |
| | | Contact: ±4KV 150pF/330Ω 5 times | | |
| 9 | Drop Test (Packaged) | Height:80 cm,1 corner, 3 edges, 6 surfaces. | 2 | GB/T2423.8-1995 |

Note1. No deflection cosmetic and operational function allowable.

Note2. Total current Consumption should be below double of initial value

13. Precautions and Warranty

13.1 Safety

13.1.1 The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

13.1.2 Since the liquid crystal cells are made of glass, do not apply strong impact on them. Handle with care.

13.2 Handling

13.2.1 Reverse and use within ratings in order to keep performance and prevent damage.

13.2.2 Do not wipe the polarizer with dry cloth, as it might cause scratch. If the surface of the LCD needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with petroleum IPA, do not use other chemicals.

13.3 Storage

13.3.1 Do not store the LCD module beyond the specified temperature ranges.

13.3.2 Strong light exposure causes degradation of polarizer and color filter.

13.4 Metal Pin (Apply to Products with Metal Pins)

13.4.1 Pins of LCD and Backlight

13.4.1.1 Solder tip can touch and press on the tip of Pin LEAD during the soldering

13.4.1.2 Recommended Soldering Conditions

Solder Type: Sn96.3~94-Ag3.3~4.3-Cu0.4~1.1



Maximum Solder Temperature: 370°C

Maximum Solder Time: 3s at the maximum temperature

Recommended Soldering Temp: 350±20°C

Typical Soldering Time: ≤3s

13.4.1.3 Solder Wetting



13.4.2 Pins of EL

13.4.2.1 Solder tip can touch and press on the tip of EL leads during soldering.

13.4.2.2 No Solder Paste on the soldering pad on the motherboard is recommended.

13.4.2.3 Recommended Soldering Conditions

Solder type: Nippon Alimit Leadfree SR-34, size 0.5mm

Recommended Solder Temperature: 270~290°C


Typical Soldering Time: ≤2s

Minimum solder distance from EL lamp (body):2.0mm


13.4.2.4 No horizontal press on the EL leads during soldering.

13.4.2.5 180° bend EL leads three times is not allowed.

13.4.2.6 Solder Wetting




Recommended




Not Recommended

13.4.2.7 The type of the solder iron:




Recommended



Not Recommended

13.4.2.8 Solder Pad



13.5 Operation

- 13.5.1 Do not drive LCD with DC voltage
- 13.5.2 Response time will increase below lower temperature
- 13.5.3 Display may change color with different temperature
- 13.5.4 Mechanical disturbance during operation, such as pressing on the display area, may cause the segments to appear “fractured”.
- 13.5.5. Do not connect or disconnect the LCM to or from the system when power is on.
- 13.5.6. Never use the LCM under abnormal condition of high temperature and high humidity.
- 13.5.7. Module has high frequency circuits. Sufficient suppression to the electromagnetic interface shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- 13.5.8. Do not display the fixed pattern for long time (we suggest the time not longer than one hour) because it may develop image sticking due to the TFT structure


13.6 Static Electricity

- 13.6.1 CMOS LSIs are equipped in this unit, so care must be taken to avoid the electro-static charge, by ground human body, etc.
- 13.6.2 The normal static prevention measures should be observed for work clothes and benches.
- 13.6.3 The module should be kept into anti-static bags or other containers resistant to static for storage.

13.7 Limited Warranty

- 13.7.1 Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss.
- 13.7.2 If possible, we suggest customer to use up all modules in six months. If the module storage time over twelve months, we suggest that recheck it before the module be used.
- 13.7.3 After the product shipped, any product quality issues must be feedback within three months, otherwise, we will not be responsible for the subsequent or consequential events.


14. Outline Drawing



NOTES:

1. Display Type: 4.6" TFT
2. Viewing Direction: 12 O' CLOCK
3. Gray Scale Inversion Direction: 6 O' CLOCK
4. Polarizer Mode: Transmissive / Normal White
5. Operation Temperature: -20° C to +70° C
6. Storage Temperature: -30° C to +80° C
7. Driver IC: ILI6126C & ILI5960D
8. Logic Power Supply Voltage: 3.3Volt (typ.)
9. Backlight; White (18xLEDS) / 19.2Volt/60mA (typ.)

Unspecification tolerance are ±0.2



| NO. | PIN NAME |
|-----|----------|
| 1 | VLED- |
| 2 | VLED+ |
| 3 | GND |
| 4 | VDD |
| 5 | R0 |
| 6 | R1 |
| 7 | R2 |
| 8 | R3 |
| 9 | R4 |
| 10 | R5 |
| 11 | R6 |
| 12 | R7 |
| 13 | G0 |
| 14 | G1 |
| 15 | G2 |
| 16 | G3 |
| 17 | G4 |
| 18 | G5 |
| 19 | G6 |
| 20 | G7 |
| 21 | B0 |
| 22 | B1 |
| 23 | B2 |
| 24 | B3 |
| 25 | B4 |
| 26 | B5 |
| 27 | B6 |
| 28 | B7 |
| 29 | GND |
| 30 | CLKIN |
| 31 | STBYB |
| 32 | HSD |
| 33 | VSD |
| 34 | DEN |
| 35 | NC |
| 36 | GND |
| 37 | XR |
| 38 | YD |
| 39 | XL |
| 40 | YU |